


Power LEDs Line IP65


Power LEDs Line IP65 605 (Both Ends Lead Wire)


Luci Pte., Ltd.

2019.08.23



The specifications are subject to change without prior notice. Unit Of Measure : mm

	Part Name	Material	Note	
1	LED		SMD type	
2	Body	Aluminum	Silver	
3	Connector	PBT	CL07D-02M, CL07D-02A	
4	Lead wire	Heat resistant fluorine electric wire	0.5sq	
5	Lens	Acrylic	Clear (Medium / Narrow)	
6	Protective cover	Polycarbonate	Clear	
7	Fixing spring	Stainless	Silver	
8	Mounting clip	Aluminum	Silver	
9	Spiral tube	Nylon	Black	
10	End clip	Stainless	Silver	
11	Cable		VCTF 0.3sq	
12	Crimped terminal		Brass, Blue	



Spec		Item Number
Input voltage : DC24V	Light Source color : White : 40 : 4000K (1140lm / Ra83)	
Power consumption : 12W	Warm white 3500K : 35 : 3500K (1140lm / Ra83)	L-ELA9K2-060J40L-24C-P
Weight : 230g	Warm white 3000K : 30 : 3000K (1130lm / Ra83)	L-ELA9K2-060J35L-24C-P
Number of LEDs : 30	Warm white 2700K : 27 : 2700K (1100lm / Ra83)	L-ELA9K2-060J30L-24C-P
Max. sets connectable : 9m		L-ELA9K2-060J27L-24C-P
Environment : Indoors,Outdoors, Bath room, Wash room		L-ELA9K2-060J40N-24C-P
(limited to places where water does not accumulate and which rainstorms do not hit directly)		L-ELA9K2-060J35N-24C-P
Accessories : Mounting screw (4pcs)		L-ELA9K2-060J30N-24C-P
Option parts : Power supply cable, Joint cable,		L-ELA9K2-060J27N-24C-P
End clip		

Job/Project Name

Area/Location/Circuit No.

Product Code

Qty.	Length(mm)
------	------------

Luci Pte. Ltd. <http://www.luci.co.jp>

E-mail: info@luci.co.jp

LUCI (SHANGHAI) LIGHTING TECHNOLOGY CO., LTD.

Singapore World HQ : Hong Kong Marketing Office

Korea Office

Shanghai China mainland Regional HQ

Tel: +65-6291-2410

Tel: +852-2219-8462 / Fax: +852-2219-8461

Tel: +82-2-508-2541

Tel: +86-21-5238-9115 / Fax: +86-21-5238-8727 / E-mail : info@luci.co.jp